CAS No: 141-32-2 MSDS



MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product form : Substance

EC index no : 607-062-00-3 : 205-480-7 EC no CAS No : 141-32-2 Product code : 00062

Formula : C7H12O2 - CH2CHCOOC4H9

Chemical structure

`CH₃

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Laboratory chemicals, Manufacture of substances

Uses advised against

No additional information available

Details of the supplier of the safety data sheet 1.3.

Labogens Fine Chem Industries 1st Floor, Above Bank of India, Guru Vihar, Rahon Road, Ludhiana Pb. (141007) +91 9316777775, +91 7707855700 sales@labogens.com - www.Labogens.com

Emergency telephone number

Emergency number : +91 7707855700 (9:00am - 6:00 pm)

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, H226 Category 3

Serious eye damage/eye H319

irritation, Category 2

Skin corrosion/irritation, H315

Category 2

Specific target organ H335

toxicity — Single

exposure, Category 3, Respiratory tract irritation

Sensitisation — Skin, H317

category 1

09/04/2015 1/11 www.Labogens.com

Safety Data Sheet

Full text of classification categories and H statements : see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

Xi; R36/37/38

R43 R10

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :





GHS02 GHS07

Signal word (CLP) : Warning

Hazard statements (CLP) : H226 - Flammable liquid and vapour

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H335 - May cause respiratory irritation

Precautionary statements (CLP) : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray

P280 - Wear protective gloves/protective clothing/eye protection/face protection P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Name : BUTYL ACRYLATE MONOMER FOR SYNTHESIS

CAS No : 141-32-2 EC no : 205-480-7 EC index no : 607-062-00-3

Full text of R- and H-phrases: see section 16

www.Labogens.com 09/04/2015 2/11

Safety Data Sheet

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific

treatment (see ... on this label). If skin irritation or rash occurs:

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

First-aid measures after ingestion : Rinse mouth out with water. If you feel unwell, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause an allergic skin reaction. May cause respiratory irritation.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2).

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.

Explosion hazard : May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked

lights. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required.

Emergency procedures : Stop release.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Collect spillage. On land, sweep or shovel into suitable containers. Soak up spills

with inert solids, such as clay or diatomaceous earth as soon as possible.

www.Labogens.com 09/04/2015 3/11

Safety Data Sheet

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

Precautions for safe handling

: Handle empty containers with care because residual vapours are flammable.

: No naked lights. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid breathing dust/fume/gas/mist/vapours/spray. Use

only outdoors or in a well-ventilated area.

Hygiene measures : Wash ... thoroughly after handling. Contaminated work clothing should not be

allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting/... equipment.

Storage conditions : Keep container tightly closed.

Incompatible materials : Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Hand protection : protective gloves

Eye protection : Chemical goggles or safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : Wear respiratory protection

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Molecular mass : 128.17 g/mol Colour : Clear Colorless.

Odour : Fruity.

Odour threshold : No data available

pH : No data available

Relative evaporation rate (butylacetate=1) : No data available

Melting point : -64.6 °C

Freezing point : No data available

www.Labogens.com 09/04/2015 4/11

Safety Data Sheet

Boiling point : 145 °C

Flash point : 36 °C

Critical temperature : 321 °C Auto-ignition temperature : 293 °C

Decomposition temperature : No data available

Flammability (solid, gas) : Flammable

Flammable liquid and vapour

Vapour pressure : 4.4 hPa at 20 °C

Relative vapour density at 20 °C : No data available

Relative density : No data available

Density : 0.894 g/cm³

Relative gas density : 4.43

Solubility : Water: slightly soluble

Log Pow : 2.38

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosive properties : No data available

Oxidising properties : No data available

Explosive limits : 0.013 - 0.099 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

www.Labogens.com 09/04/2015 5/11

Safety Data Sheet

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single

exposure)

: May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

BUTYL ACRYLATE MONOMER FOR SYNTHESIS (141-32-2)	
Log Pow	2.38

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal

recommendations

: Dispose of contents/container to ...

Additional information : Handle empty containers with care because residual vapours are flammable.

www.Labogens.com 09/04/2015 6/11

Safety Data Sheet

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 2348 UN-No. (IMDG) : 2348 UN-No.(IATA) : 2348 UN-No. (ADN) : 2348 UN-No. (RID) : 2348

14.2. UN proper shipping name

Proper Shipping Name (ADR)

Proper Shipping Name (IMDG)

Proper Shipping Name (IATA)

Proper Shipping Name (IATA)

Proper Shipping Name (ADN)

BUTYL ACRYLATES, STABILIZED

Transport document description (ADR) : UN 2348 BUTYL ACRYLATES, STABILIZED, 3, III, (D/E) Transport document description (IMDG) : UN 2348 BUTYL ACRYLATES, STABILIZED, 3, III (36°C c.c.)

Transport document description (IATA) : UN 2348 BUTYL ACRYLATES, STABILIZED, 3, III

Transport document description (ADN) : UN 2348 BUTYL ACRYLATES, STABILIZED, 3, III

Transport document description (RID) : UN 2348 BUTYL ACRYLATES, STABILIZED, 3, III

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



ADN

Transport hazard class(es) (ADN) : 3

www.Labogens.com 09/04/2015 7/11

Safety Data Sheet

Danger labels (ADN) : 3



RID

Transport hazard class(es) (RID) : 3
Danger labels (RID) : 3



14.4. Packing group

Packing group (ADR) : III
Packing group (IMDG) : III
Packing group (IATA) : III
Packing group (ADN) : III
Packing group (RID) : III

14.5. Environmental hazards

Dangerous for the environment : No Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1
Limited quantities (ADR) : 5L
Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Mixed packing provisions (ADR) : MP19
Portable tank and bulk container : T2

instructions (ADR)

Portable tank and bulk container special : TP1

provisions (ADR)

Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Packages : V12

(ADR)

Special provisions for carriage - Operation : S2

(ADR)

Hazard identification number (Kemler No.) : 39

Orange plates :

39 2348

Tunnel restriction code (ADR) : D/E EAC code : 3W

www.Labogens.com 09/04/2015 8/11

: A

Safety Data Sheet

APP code : A(fl)

- Transport by sea

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : P001, LP01
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-D

Flash point (IMDG) : 36°C to 41°C c.c.

MFAG-No : 130P

- Air transport

Stowage category (IMDG)

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity : 10L

(IATA)

PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
ERG code (IATA) : 3L

- Inland waterway transport

Classification code (ADN) : F1
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01

Number of blue cones/lights (ADN) : 0

- Rail transport

Classification code (RID) : F1
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Mixed packing provisions (RID) : MP19
Portable tank and bulk container : T2

instructions (RID)

Portable tank and bulk container special

provisions (RID)

: TP1

Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages : W12

(RID)

Colis express (express parcels) (RID) : CE4 Hazard identification number (RID) : 39

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

www.Labogens.com 09/04/2015 9/11

Safety Data Sheet

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions

BUTYL ACRYLATE MONOMER FOR SYNTHESIS is not on the REACH Candidate List BUTYL ACRYLATE MONOMER FOR SYNTHESIS is not on the REACH Annex XIV List

15.1.2. National regulations

Germany

AwSV/VwVwS Annex reference : Water hazard class (WGK) 1, slightly hazardous to water (Classification according to

VwVwS, Annex 2; WGK No 12)

Immission Control Act - 12.BImSchV

12th Ordinance Implementing the Federal : Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

Denmark

Class for fire hazard : Class II-1 Store unit : 5 liter

: R10 <H226;H315;H317;H319;H335>; Emergency management guidelines for the Classification remarks

storage of flammable liquids must be followed

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product

Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of R-, H- and EUH-phrases:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H335	May cause respiratory irritation
R10	Flammable

09/04/2015 10/11 www.Labogens.com

Safety Data Sheet

R36/37/38	Irritating to eyes, respiratory system and skin
R43	May cause sensitisation by skin contact
Xi	Irritant

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

www.Labogens.com 09/04/2015 11/11