

CARBOL FUCHSIN DILUTE STAINING SOLUTION MSDS



CAS-No.: MSDS

MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
:
Product code : 02521

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial
For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Labogens Fine Chem Industries
1st Floor , Above Bank of India, Guru Vihar , Rahon Road,
Ludhiana Pb. (141007)
+91 9316777775, +91 7707855700
sales@labogens.com - www.Labogens.com

1.4. Emergency telephone number

Emergency number : +91 7707855700 (9:00am - 6:00 pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, H226
Category 3
Acute toxicity (inhal.), H332
Category 4
Skin corrosion/irritation, H314
Category 1
Germ cell mutagenicity, H341
Category 2

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

CARBOL FUCHSIN DILUTE STAINING SOLUTION

Safety Data Sheet

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS05

GHS07

GHS08

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H226 - Flammable liquid and vapour.
H314 - Causes severe skin burns and eye damage.
H332 - Harmful if inhaled.
H341 - Suspected of causing genetic defects.

Precautionary statements (CLP) :

P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a doctor.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Water	(CAS-No.) 7732-18-5 (EC-No.) 231-791-2	>= 99	Not classified
C.I. Basic Red 9	(CAS-No.) 569-61-9 (EC-No.) 209-321-2 (EC Index-No.) 611-031-00-X	0.01 - 1	Carc. 1B, H350
Phenol	(CAS-No.) 108-95-2 (EC-No.) 203-632-7 (EC Index-No.) 604-001-00-2	0.01 - 1	Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Oral), H301 Skin Corr. 1B, H314 Eye Dam. 1, H318 Muta. 2, H341 STOT RE 2, H373
Ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5	0.01 - 1	Flam. Liq. 3, H226 Skin Corr. 1A, H314

CARBOL FUCHSIN DILUTE STAINING SOLUTION

Safety Data Sheet

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Allow affected person to breathe fresh air. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Wash with plenty of water/.... Get immediate medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes severe skin burns and eye damage. Suspected of causing genetic defects.
Symptoms/effects after inhalation	: Harmful if inhaled.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Dry powder. Foam. Water spray.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
--------------------------------	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: No open flames. No smoking. Remove ignition sources. Use special care to avoid static electric charges.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Use personal protective equipment as required.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Collect spillage. On land, sweep or shovel into suitable containers.
-------------------------	--

6.4. Reference to other sections

No additional information available

CARBOL FUCHSIN DILUTE STAINING SOLUTION

Safety Data Sheet

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Use personal protective equipment as required. Avoid contact with skin and eyes. Do not breathe vapours. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge.
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep container tightly closed. Keep in fireproof place.
Incompatible materials	: Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Hand protection	: Protective gloves
Eye protection	: Chemical goggles or safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: [In case of inadequate ventilation] wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Dark red.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: -114.1 °C
Freezing point	: No data available
Boiling point	: 78.5 °C
Flash point	: 12.78 °C
Critical temperature	: 243 °C
Auto-ignition temperature	: 363 °C
Decomposition temperature	: No data available

CARBOL FUCHSIN DILUTE STAINING SOLUTION

Safety Data Sheet

Flammability (solid, gas)	: Flammable
Vapour pressure	: 2.61 kPa (at 20°C)
Relative vapour density at 20 °C	: 1.59
Relative density	: No data available
Density	: 0.98 g/cm ³
Solubility	: Water: Easily soluble in cold water
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 0.033 - 0.19 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled.

ATE CLP (gases)	4500 ppmv/4h
ATE CLP (vapours)	11 mg/l/4h
ATE CLP (dust,mist)	1.5 mg/l/4h

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Serious eye damage, category 1, implicit
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Suspected of causing genetic defects.

CARBOL FUCHSIN DILUTE STAINING SOLUTION

Safety Data Sheet

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

No additional information available

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 2924

UN-No. (IMDG) : 2924

UN-No. (IATA) : 2924

UN-No. (ADN) : 2924

UN-No. (RID) : 2924

CARBOL FUCHSIN DILUTE STAINING SOLUTION

Safety Data Sheet

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Proper Shipping Name (IATA)	: Flammable liquid, corrosive, n.o.s.
Proper Shipping Name (ADN)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Proper Shipping Name (RID)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Transport document description (ADR)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S., 3 (8), III, (D/E)
Transport document description (IMDG)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S., 3 (8), III
Transport document description (IATA)	: UN 2924 Flammable liquid, corrosive, n.o.s., 3 (8), III
Transport document description (ADN)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S., 3 (8), III
Transport document description (RID)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S., 3 (8), III

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 3 (8)
Danger labels (ADR)	: 3, 8



IMDG

Transport hazard class(es) (IMDG)	: 3 (8)
Danger labels (IMDG)	: 3, 8



IATA

Transport hazard class(es) (IATA)	: 3 (8)
Hazard labels (IATA)	: 3, 8



ADN

Transport hazard class(es) (ADN)	: 3 (8)
Danger labels (ADN)	: 3, 8



RID

Transport hazard class(es) (RID)	: 3 (8)
----------------------------------	---------

CARBOL FUCHSIN DILUTE STAINING SOLUTION

Safety Data Sheet

Danger labels (RID) : 3, 8



14.4. Packing group


Packing group (ADR) : III
Packing group (IMDG) : III
Packing group (IATA) : III
Packing group (ADN) : III
Packing group (RID) : III

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : FC
Special provisions (ADR) : 274
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, R001
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T7
Portable tank and bulk container special provisions (ADR) : TP1, TP28
Tank code (ADR) : L4BN
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 38
Orange plates : 
Tunnel restriction code (ADR) : D/E
EAC code : •3WE
APP code : A(fl)

- Transport by sea

Special provisions (IMDG) : 223, 274
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T7

CARBOL FUCHSIN DILUTE STAINING SOLUTION

Safety Data Sheet

Tank special provisions (IMDG)	: TP1, TP28
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-C
Stowage category (IMDG)	: A
Stowage and handling (IMDG)	: SW2
MFAG-No	: 132

- Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y342
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 354
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 365
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3C

- Inland waterway transport

Classification code (ADN)	: FC
Special provisions (ADN)	: 274
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

- Rail transport

Classification code (RID)	: FC
Special provisions (RID)	: 274
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T7
Portable tank and bulk container special provisions (RID)	: TP1, TP28
Tank codes for RID tanks (RID)	: L4BN
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 38

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

CARBOL FUCHSIN DILUTE STAINING SOLUTION

Safety Data Sheet

Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

Reference to AwSV : Water hazard class (WGK) 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : C.I. Basic Red 9, Phenol, Ethanol are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : Ethanol is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : Ethanol is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Ethanol is listed

Denmark

Class for fire hazard : Class I-1

Store unit : 1 liter

Classification remarks : F <Flam. Liq. 3>; Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Carc. 1B	Carcinogenicity, Category 1B

CARBOL FUCHSIN DILUTE STAINING SOLUTION

Safety Data Sheet

Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Skin Corr. 1	Skin corrosion/irritation, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.