

MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Substance
	:
EC index no	: 601-037-00-0
EC no	: 203-777-6
CAS No	: 110-54-3
Product code	: 00160
Formula	: C6H14 - CH3(CH2)4CH3

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Industrial. For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Labogens Fine Chem Industries
1st Floor , Above Bank of India, Guru Vihar , Rahon Road,
Ludhiana Pb. (141007)
+91 9316777775, +91 7707855700
sales@labogens.com - www.Labogens.com

1.4. Emergency telephone number

Emergency number : +91 7707855700 (9:00am - 6:00 pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2	H225
Aspiration hazard, Category 1	H304
Reproductive toxicity, Category 2	H361f
Skin corrosion/irritation, Category 2	H315
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity — Repeated exposure, Category 2	H373
Specific target organ	H336

HEXANE 65-70°C

Safety Data Sheet

toxicity — Single exposure, Category 3, Narcosis
Hazardous to the aquatic environment — Chronic Hazard, Category 2

Full text of classification categories and H statements : see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

Repr.Cat.3; R62
F; R11
Xn; R65
Xn; R48/20
Xi; R38
N; R51/53
R67

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS08

GHS07

GHS09

Signal word (CLP) : Danger

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H361f - Suspected of damaging fertility
H373 - May cause damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting/... equipment
P260 - Do not breathe dust/fume/gas/mist/vapours/spray
P264 - Wash ... thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
P302+P352 - IF ON SKIN: Wash with plenty of water/...
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

HEXANE 65-70°C

Safety Data Sheet

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P308+P313 - IF exposed or concerned: Get medical advice/attention
P312 - Call a POISON CENTER/doctor/... if you feel unwell
P321 - Specific treatment (see ... on this label)
P331 - Do NOT induce vomiting
P332+P313 - If skin irritation occurs: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use ... to extinguish
P391 - Collect spillage
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to ...

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Name	: HEXANE 65-70°C
CAS No	: 110-54-3
EC no	: 203-777-6
EC index no	: 601-037-00-0

Full text of R- and H-phrases: see section 16

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see ... on this label).
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Suspected of damaging fertility. Causes damage to organs.
Symptoms/injuries after inhalation	: May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

HEXANE 65-70°C

Safety Data Sheet

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.
Explosion hazard : May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Avoid breathing dust/fume/gas/mist/vapours/spray.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Collect spillage. On land, sweep or shovel into suitable containers. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling : No naked lights. No smoking. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.
Hygiene measures : Wash ... thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/... equipment.
Storage conditions : Keep in fireproof place. Keep container tightly closed. Store in original container. Store in a dry place. Protect from moisture.
Incompatible materials : Heat sources.

7.3. Specific end use(s)

No additional information available

HEXANE 65-70°C

Safety Data Sheet

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Hand protection	: protective gloves
Eye protection	: Chemical goggles or safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: Wear respiratory protection

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Molecular mass	: 86.18 g/mol
Colour	: Clear Colorless.
Odour	: gasoline-like.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: -95 °C
Freezing point	: No data available
Boiling point	: 68 - 70
Flash point	: -23 °C
Auto-ignition temperature	: 225 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable Highly flammable liquid and vapour
Vapour pressure	: 151 mm Hg at 25 deg C
Relative vapour density at 20 °C	: 2.97
Relative density	: No data available
Density	: 0.678 g/cm ³
Solubility	: Water: Insoluble in water
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 0.31 mPa.s 20 deg C

HEXANE 65-70°C

Safety Data Sheet

Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 0.011 - 0.075 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Open flame. Direct sunlight. Overheating. Heat. Sparks.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility.
Specific target organ toxicity (single exposure)	: May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.

HEXANE 65-70°C (110-54-3)

Viscosity, kinematic	0.45722714 mm ² /s
----------------------	-------------------------------

HEXANE 65-70°C

Safety Data Sheet

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

HEXANE 65-70°C (110-54-3)

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to ...

Additional information : Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials : Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1208

UN-No. (IMDG) : 1208

UN-No.(IATA) : 1208

UN-No.(ADN) : 1208

UN-No. (RID) : 1208

14.2. UN proper shipping name

Proper Shipping Name (ADR) : HEXANES

Proper Shipping Name (IMDG) : HEXANES

Proper Shipping Name (IATA) : HEXANES

Proper Shipping Name (ADN) : HEXANES

Proper Shipping Name (RID) : HEXANES

Transport document description (ADR) : UN 1208 HEXANES, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS

Transport document description (IMDG) : UN 1208 HEXANES, 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS

HEXANE 65-70°C

Safety Data Sheet

Transport document description (IATA) : UN 1208 HEXANES, 3, II, ENVIRONMENTALLY HAZARDOUS
Transport document description (ADN) : UN 1208 HEXANES, 3, II, ENVIRONMENTALLY HAZARDOUS
Transport document description (RID) : UN 1208 HEXANES, 3, II, ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



ADN

Transport hazard class(es) (ADN) : 3
Danger labels (ADN) : 3



RID

Transport hazard class(es) (RID) : 3
Danger labels (RID) : 3



14.4. Packing group

Packing group (ADR) : II
Packing group (IMDG) : II

HEXANE 65-70°C

Safety Data Sheet


Packing group (IATA)	: II
Packing group (ADN)	: II
Packing group (RID)	: II

14.5. Environmental hazards

Dangerous for the environment	: Yes
Marine pollutant	: Yes
Other information	: No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	: F1
Limited quantities (ADR)	: 1L
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	: 
Tunnel restriction code (ADR)	: D/E
EAC code	: 3YE

- Transport by sea

Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: E
MFAG-No	: 128

- Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L

HEXANE 65-70°C

Safety Data Sheet

ERG code (IATA) : 3H

- Inland waterway transport

Classification code (ADN) : F1
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E2
Carriage permitted (ADN) : T
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 1

- Rail transport

Classification code (RID) : F1
Limited quantities (RID) : 1L
Excepted quantities (RID) : E2
Packing instructions (RID) : P001, IBC02, R001
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions (RID) : TP1
Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 2
Colis express (express parcels) (RID) : CE7
Hazard identification number (RID) : 33

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions
HEXANE 65-70°C is not on the REACH Candidate List
HEXANE 65-70°C is not on the REACH Annex XIV List

15.1.2. National regulations

Germany

AwSV/VwVwS Annex reference : Water hazard class (WGK) 2, hazardous to water (Classification according to VwVwS, Annex 2; WGK No 124)
12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

HEXANE 65-70°C

Safety Data Sheet

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of R-, H- and EUH-phrases:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H361f	Suspected of damaging fertility
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
R11	Highly flammable
R38	Irritating to skin
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R62	Possible risk of impaired fertility
R65	Harmful: may cause lung damage if swallowed
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product